
pygeos

Casper van der Wel

Sep 28, 2020

CONTENTS:

1	Why ufuncs?	3
2	The Geometry object	5
3	API Reference	7
3.1	<code>pygeos.constructive</code>	7
3.2	<code>pygeos.coordinates</code>	13
3.3	<code>pygeos.geometry</code>	14
3.4	<code>pygeos.linear</code>	20
3.5	<code>pygeos.measurement</code>	22
3.6	<code>pygeos.predicates</code>	24
3.7	<code>pygeos.set_operations</code>	34
3.8	<code>pygeos.strtree</code>	37
4	Indices and tables	39
	Python Module Index	41
	Index	43

PyGEOS is a C/Python library with vectorized geometry functions. The geometry operations are done in the open-source geometry library GEOS. PyGEOS wraps these operations in NumPy ufuncs providing a performance improvement when operating on arrays of geometries.

WHY UFUNCS?

A universal function (or ufunc for short) is a function that operates on n-dimensional arrays in an element-by-element fashion, supporting array broadcasting. The for-loops that are involved are fully implemented in C diminishing the overhead of the Python interpreter.

THE GEOMETRY OBJECT

The *pygeos.Geometry* object is a container of the actual GEOSGeometry object. A C pointer to this object is stored in a static attribute of the *Geometry* object. This keeps the python interpreter out of the ufunc inner loop. The *Geometry* object keeps track of the underlying GEOSGeometry and allows the python garbage collector to free memory when it is not used anymore.

Geometry objects are immutable. Construct them as follows:

```
>>> from pygeos import Geometry
>>> geometry = Geometry("POINT (5.2 52.1)")
```

Or using one of the provided (vectorized) functions:

```
>>> from pygeos import points
>>> point = points(5.2, 52.1)
```


API REFERENCE

3.1 pygeos.constructive

`pygeos.constructive.boundary(geometry, **kwargs)`

Returns the topological boundary of a geometry.

Parameters `geometry` : Geometry or array_like

This function will raise for non-empty geometrycollections.

Examples

```
>>> boundary(Geometry("POINT (0 0)"))
<pygeos.Geometry GEOMETRYCOLLECTION EMPTY>
>>> boundary(Geometry("LINESTRING(0 0, 1 1, 1 2)"))
<pygeos.Geometry MULTIPOINT (0 0, 1 2)>
>>> boundary(Geometry("LINEARRING (0 0, 1 0, 1 1, 0 1, 0 0)"))
<pygeos.Geometry MULTIPOINT EMPTY>
>>> boundary(Geometry("POLYGON((0 0, 1 0, 1 1, 0 1, 0 0))"))
<pygeos.Geometry LINESTRING (0 0, 1 0, 1 1, 0 1, 0 0)>
>>> boundary(Geometry("MULTIPOINT (0 0, 1 2)")) is None
True
```

`pygeos.constructive.buffer(geometry, radius, quadsegs=8, cap_style='round', join_style='round', mitre_limit=5.0, single_sided=False, **kwargs)`

Computes the buffer of a geometry for positive and negative buffer radius.

The buffer of a geometry is defined as the Minkowski sum (or difference, for negative width) of the geometry with a circle with radius equal to the absolute value of the buffer radius.

The buffer operation always returns a polygonal result. The negative or zero-distance buffer of lines and points is always empty.

Parameters `geometry` : Geometry or array_like

width : float or array_like

Specifies the circle radius in the Minkowski sum (or difference).

quadsegs : int

Specifies the number of linear segments in a quarter circle in the approximation of circular arcs.

cap_style : {'round', 'square', 'flat'}

Specifies the shape of buffered line endings. ‘round’ results in circular line endings (see `quadsegs`). Both ‘square’ and ‘flat’ result in rectangular line endings, only ‘flat’ will end at the original vertex, while ‘square’ involves adding the buffer width.

join_style : { ‘round’, ‘bevel’, ‘sharp’ }

Specifies the shape of buffered line midpoints. ‘round’ results in rounded shapes. ‘bevel’ results in a beveled edge that touches the original vertex. ‘mitre’ results in a single vertex that is beveled depending on the `mitre_limit` parameter.

mitre_limit : float

Crops of ‘mitre’-style joins if the point is displaced from the buffered vertex by more than this limit.

single_sided : bool

Only buffer at one side of the geometry.

Examples

```
>>> buffer(Geometry("POINT (10 10)"), 2, quadsegs=1)
<pygeos.Geometry POLYGON ((12 10, 10 8, 8 10, 10 12, 12 10))>
>>> buffer(Geometry("POINT (10 10)"), 2, quadsegs=2)
<pygeos.Geometry POLYGON ((12 10, 11.4 8.59, 10 8, 8.59 8.59, 8 10, 8.59 11.4, 10
↪12, 11.4 11.4, 12 10))>
>>> buffer(Geometry("POINT (10 10)"), -2, quadsegs=1)
<pygeos.Geometry POLYGON EMPTY>
>>> line = Geometry("LINESTRING (10 10, 20 10)")
>>> buffer(line, 2, cap_style="square")
<pygeos.Geometry POLYGON ((20 12, 22 12, 22 8, 10 8, 8 8, 8 12, 20 12))>
>>> buffer(line, 2, cap_style="flat")
<pygeos.Geometry POLYGON ((20 12, 20 8, 10 8, 10 12, 20 12))>
>>> buffer(line, 2, single_sided=True, cap_style="flat")
<pygeos.Geometry POLYGON ((20 10, 10 10, 10 12, 20 12, 20 10))>
>>> line2 = Geometry("LINESTRING (10 10, 20 10, 20 20)")
>>> buffer(line2, 2, cap_style="flat", join_style="bevel")
<pygeos.Geometry POLYGON ((18 12, 18 20, 22 20, 22 10, 20 8, 10 8, 10 12, 18 12))>
>>> buffer(line2, 2, cap_style="flat", join_style="mitre")
<pygeos.Geometry POLYGON ((18 12, 18 20, 22 20, 22 8, 10 8, 10 12, 18 12))>
>>> buffer(line2, 2, cap_style="flat", join_style="mitre", mitre_limit=1)
<pygeos.Geometry POLYGON ((18 12, 18 20, 22 20, 21.8 9, 21 8.17, 10 8, 10 12, 18
↪12))>
>>> square = Geometry("POLYGON((0 0, 10 0, 10 10, 0 10, 0 0))")
>>> buffer(square, 2, join_style="mitre")
<pygeos.Geometry POLYGON ((-2 -2, -2 12, 12 12, 12 -2, -2 -2))>
>>> buffer(square, -2, join_style="mitre")
<pygeos.Geometry POLYGON ((2 2, 2 8, 8 8, 8 2, 2 2))>
>>> buffer(square, -5, join_style="mitre")
<pygeos.Geometry POLYGON EMPTY>
>>> buffer(line, float("nan")) is None
True
```

`pygeos.constructive.centroid(geometry, **kwargs)`

Computes the geometric center (center-of-mass) of a geometry.

For multipoints this is computed as the mean of the input coordinates. For multilinestrings the centroid is weighted by the length of each line segment. For multipolygons the centroid is weighted by the area of each polygon.

Parameters *geometry* : Geometry or array_like

Examples

```
>>> centroid(Geometry("POLYGON ((0 0, 10 0, 10 10, 0 10, 0 0))"))
<pygeos.Geometry POINT (5 5)>
>>> centroid(Geometry("LINESTRING (0 0, 2 2, 10 10)"))
<pygeos.Geometry POINT (5 5)>
>>> centroid(Geometry("MULTIPOINT (0 0, 10 10)"))
<pygeos.Geometry POINT (5 5)>
>>> centroid(Geometry("POLYGON EMPTY"))
<pygeos.Geometry POINT EMPTY>
```

`pygeos.constructive.convex_hull(geometry, **kwargs)`
 Computes the minimum convex geometry that encloses an input geometry.

Parameters *geometry* : Geometry or array_like

Examples

```
>>> convex_hull(Geometry("MULTIPOINT (0 0, 10 0, 10 10)"))
<pygeos.Geometry POLYGON ((0 0, 10 10, 10 0, 0 0))>
>>> convex_hull(Geometry("POLYGON EMPTY"))
<pygeos.Geometry GEOMETRYCOLLECTION EMPTY>
```

`pygeos.constructive.delaunay_triangles(geometry, tolerance=0.0, only_edges=False, **kwargs)`

Computes a Delaunay triangulation around the vertices of an input geometry.

The output is a geometrycollection containing polygons (default) or linestrings (see `only_edges`). Returns an `None` if an input geometry contains less than 3 vertices.

Parameters *geometry* : Geometry or array_like

tolerance : float or array_like

Snap input vertices together if their distance is less than this value.

only_edges : bool or array_like

If set to `True`, the triangulation will return a collection of linestrings instead of polygons.

Examples

```
>>> points = Geometry("MULTIPOINT (50 30, 60 30, 100 100)")
>>> delaunay_triangles(points)
<pygeos.Geometry GEOMETRYCOLLECTION (POLYGON ((50 30, 60 30, 100 100, 50 30)))>
>>> delaunay_triangles(points, only_edges=True)
<pygeos.Geometry MULTILINESTRING ((50 30, 100 100), (50 30, 60 30), (60 30, 100
↪100))>
>>> delaunay_triangles(Geometry("MULTIPOINT (50 30, 51 30, 60 30, 100 100)"),
↪tolerance=2)
<pygeos.Geometry GEOMETRYCOLLECTION (POLYGON ((50 30, 60 30, 100 100, 50 30)))>
>>> delaunay_triangles(Geometry("POLYGON ((50 30, 60 30, 100 100, 50 30))"))
<pygeos.Geometry GEOMETRYCOLLECTION (POLYGON ((50 30, 60 30, 100 100, 50 30)))>
>>> delaunay_triangles(Geometry("LINESTRING (50 30, 60 30, 100 100)"))
```

(continues on next page)

(continued from previous page)

```
<pygeos.Geometry GEOMETRYCOLLECTION (POLYGON ((50 30, 60 30, 100 100, 50 30)))>
>>> delaunay_triangles(Geometry("GEOMETRYCOLLECTION EMPTY"))
<pygeos.Geometry GEOMETRYCOLLECTION EMPTY>
```

`pygeos.constructive.envelope(geometry, **kwargs)`

Computes the minimum bounding box that encloses an input geometry.

Parameters `geometry` : Geometry or array_like

Examples

```
>>> envelope(Geometry("LINESTRING (0 0, 10 10)"))
<pygeos.Geometry POLYGON ((0 0, 10 0, 10 10, 0 10, 0 0))>
>>> envelope(Geometry("MULTIPOINT (0 0, 10 0, 10 10)"))
<pygeos.Geometry POLYGON ((0 0, 10 0, 10 10, 0 10, 0 0))>
>>> envelope(Geometry("POINT (0 0)"))
<pygeos.Geometry POINT (0 0)>
>>> envelope(Geometry("GEOMETRYCOLLECTION EMPTY"))
<pygeos.Geometry POINT EMPTY>
```

`pygeos.constructive.extract_unique_points(geometry, **kwargs)`

Returns all distinct vertices of an input geometry as a multipoint.

Note that only 2 dimensions of the vertices are considered when testing for equality.

Parameters `geometry` : Geometry or array_like

Examples

```
>>> extract_unique_points(Geometry("POINT (0 0)"))
<pygeos.Geometry MULTIPOINT (0 0)>
>>> extract_unique_points(Geometry("LINESTRING(0 0, 1 1, 1 1)"))
<pygeos.Geometry MULTIPOINT (0 0, 1 1)>
>>> extract_unique_points(Geometry("POLYGON((0 0, 1 0, 1 1, 0 0))"))
<pygeos.Geometry MULTIPOINT (0 0, 1 0, 1 1)>
>>> extract_unique_points(Geometry("MULTIPOINT (0 0, 1 1, 0 0)"))
<pygeos.Geometry MULTIPOINT (0 0, 1 1)>
>>> extract_unique_points(Geometry("LINESTRING EMPTY"))
<pygeos.Geometry MULTIPOINT EMPTY>
```

`pygeos.constructive.point_on_surface(geometry, **kwargs)`

Returns a point that intersects an input geometry.

Parameters `geometry` : Geometry or array_like

Examples

```
>>> point_on_surface(Geometry("POLYGON ((0 0, 10 0, 10 10, 0 10, 0 0))"))
<pygeos.Geometry POINT (5 5)>
>>> point_on_surface(Geometry("LINESTRING (0 0, 2 2, 10 10)"))
<pygeos.Geometry POINT (2 2)>
>>> point_on_surface(Geometry("MULTIPOINT (0 0, 10 10)"))
<pygeos.Geometry POINT (0 0)>
>>> point_on_surface(Geometry("POLYGON EMPTY"))
<pygeos.Geometry POINT EMPTY>
```

`pygeos.constructive.simplify(geometry, tolerance, preserve_topology=False, **kwargs)`

Returns a simplified version of an input geometry using the Douglas-Peucker algorithm.

Parameters `geometry` : Geometry or array_like

`tolerance` : float or array_like

The maximum allowed geometry displacement. The higher this value, the smaller the number of vertices in the resulting geometry.

`preserve_topology` : bool

If set to True, the operation will avoid creating invalid geometries.

Examples

```
>>> line = Geometry("LINESTRING (0 0, 1 10, 0 20)")
>>> simplify(line, tolerance=0.9)
<pygeos.Geometry LINESTRING (0 0, 1 10, 0 20)>
>>> simplify(line, tolerance=1)
<pygeos.Geometry LINESTRING (0 0, 0 20)>
>>> polygon_with_hole = Geometry("POLYGON((0 0, 0 10, 10 10, 10 0, 0 0), (2 2, 2_
↪4, 4 4, 4 2, 2 2))")
>>> simplify(polygon_with_hole, tolerance=4, preserve_topology=True)
<pygeos.Geometry POLYGON ((0 0, 0 10, 10 10, 10 0, 0 0), (2 2, 2 4, 4 4, 4 2, 2_
↪2))>
>>> simplify(polygon_with_hole, tolerance=4, preserve_topology=False)
<pygeos.Geometry POLYGON ((0 0, 0 10, 10 10, 10 0, 0 0))>
```

`pygeos.constructive.snap(geometry, reference, tolerance, **kwargs)`

Snaps an input geometry to reference geometry's vertices.

The tolerance is used to control where snapping is performed. The result geometry is the input geometry with the vertices snapped. If no snapping occurs then the input geometry is returned unchanged.

Parameters `geometry` : Geometry or array_like

`reference` : Geometry or array_like

`tolerance` : float or array_like

Examples

```
>>> point = Geometry("POINT (0 2)")
>>> snap(Geometry("POINT (0.5 2.5)"), point, tolerance=1)
<pygeos.Geometry POINT (0 2)>
>>> snap(Geometry("POINT (0.5 2.5)"), point, tolerance=0.49)
<pygeos.Geometry POINT (0.5 2.5)>
>>> polygon = Geometry("POLYGON ((0 0, 0 10, 10 10, 10 0, 0 0))")
>>> snap(polygon, Geometry("POINT (8 10)"), tolerance=5)
<pygeos.Geometry POLYGON ((0 0, 0 10, 8 10, 10 0, 0 0))>
>>> snap(polygon, Geometry("LINESTRING (8 10, 8 0)"), tolerance=5)
<pygeos.Geometry POLYGON ((0 0, 0 10, 8 10, 8 0, 0 0))>
```

`pygeos.constructive.voronoi_polygons(geometry, tolerance=0.0, extend_to=None, only_edges=False, **kwargs)`

Computes a Voronoi diagram from the vertices of an input geometry.

The output is a geometrycollection containing polygons (default) or linestrings (see `only_edges`). Returns empty if an input geometry contains less than 2 vertices or if the provided extent has zero area.

Parameters `geometry` : Geometry or array_like

`tolerance` : float or array_like

Snap input vertices together if their distance is less than this value.

`extend_to` : Geometry or array_like

If provided, the diagram will be extended to cover the envelope of this geometry (unless this envelope is smaller than the input geometry).

`only_edges` : bool or array_like

If set to True, the triangulation will return a collection of linestrings instead of polygons.

Examples

```
>>> points = Geometry("MULTIPOINT (2 2, 4 2)")
>>> voronoi_polygons(points)
<pygeos.Geometry GEOMETRYCOLLECTION (POLYGON ((3 0, 0 0, 0 4, 3 4, 3 0)), POLYGON_
↪ ((3 4, 6 4, 6 0, 3 0, 3 4)))>
>>> voronoi_polygons(points, only_edges=True)
<pygeos.Geometry LINESTRING (3 4, 3 0)>
>>> voronoi_polygons(Geometry("MULTIPOINT (2 2, 4 2, 4.2 2)"), 0.5, only_
↪ edges=True)
<pygeos.Geometry LINESTRING (3 4.2, 3 -0.2)>
>>> voronoi_polygons(points, extend_to=Geometry("LINESTRING (0 0, 10 10)"), only_
↪ edges=True)
<pygeos.Geometry LINESTRING (3 10, 3 0)>
>>> voronoi_polygons(Geometry("LINESTRING (2 2, 4 2)"), only_edges=True)
<pygeos.Geometry LINESTRING (3 4, 3 0)>
>>> voronoi_polygons(Geometry("POINT (2 2)"))
<pygeos.Geometry GEOMETRYCOLLECTION EMPTY>
```


3.2 pygeos.coordinates

`pygeos.coordinates.apply(geometry, transformation)`

Returns a copy of a geometry array with a function applied to its coordinates.

All returned geometries will be two-dimensional; the third dimension will be discarded, if present.

Parameters `geometry` : Geometry or array_like

transformation : function

A function that transforms a (N, 2) ndarray of float64 to another (N, 2) ndarray of float64.

Examples

```
>>> apply(Geometry("POINT (0 0)"), lambda x: x + 1)
<pygeos.Geometry POINT (1 1)>
>>> apply(Geometry("LINESTRING (2 2, 4 4)"), lambda x: x * [2, 3])
<pygeos.Geometry LINESTRING (4 6, 8 12)>
>>> apply(None, lambda x: x) is None
True
>>> apply([Geometry("POINT (0 0)"), None], lambda x: x).tolist()
[<pygeos.Geometry POINT (0 0)>, None]
```

`pygeos.coordinates.count_coordinates(geometry)`

Counts the number of coordinate pairs in a geometry array.

Parameters `geometry` : Geometry or array_like

Examples

```
>>> count_coordinates(Geometry("POINT (0 0)"))
1
>>> count_coordinates(Geometry("LINESTRING (2 2, 4 4)"))
2
>>> count_coordinates(None)
0
>>> count_coordinates([Geometry("POINT (0 0)"), None])
1
```

`pygeos.coordinates.get_coordinates(geometry)`

Gets coordinates from a geometry array as an array of floats.

The shape of the returned array is (N, 2), with N being the number of coordinate pairs. Three-dimensional data is ignored.

Parameters `geometry` : Geometry or array_like

Examples

```
>>> get_coordinates(Geometry("POINT (0 0)").tolist()
[[0.0, 0.0]]
>>> get_coordinates(Geometry("LINESTRING (2 2, 4 4)").tolist()
[[2.0, 2.0], [4.0, 4.0]]
>>> get_coordinates(None)
array([], shape=(0, 2), dtype=float64)
```

`pygeos.coordinates.set_coordinates(geometry, coordinates)`

Returns a copy of a geometry array with different coordinates.

All returned geometries will be two-dimensional; the third dimension will be discarded, if present.

Parameters `geometry` : Geometry or array_like

coordinates: array_like

Examples

```
>>> set_coordinates(Geometry("POINT (0 0)"), [[1, 1]])
<pygeos.Geometry POINT (1 1)>
>>> set_coordinates([Geometry("POINT (0 0)"), Geometry("LINESTRING (0 0, 0 0)"),
↳ [[1, 2], [3, 4], [5, 6]]).tolist()
[<pygeos.Geometry POINT (1 2)>, <pygeos.Geometry LINESTRING (3 4, 5 6)>]
>>> set_coordinates([None, Geometry("POINT (0 0)"), [1, 2]].tolist()
[None, <pygeos.Geometry POINT (1 2)>]
```

3.3 `pygeos.geometry`

`pygeos.geometry.get_coordinate_dimensions(geometry)`

Returns the dimensionality of the coordinates in a geometry (2 or 3).

Returns -1 for not-a-geometry values.

Parameters `geometry` : Geometry or array_like

Examples

```
>>> get_coordinate_dimensions(Geometry("POINT (0 0)"))
2
>>> get_coordinate_dimensions(Geometry("POINT Z (0 0 0)"))
3
>>> get_coordinate_dimensions(None)
-1
```

`pygeos.geometry.get_dimensions(geometry)`

Returns the inherent dimensionality of a geometry.

The inherent dimension is 0 for points, 1 for linestrings and linearrings, and 2 for polygons. For geometrycollections it is the max of the containing elements. Empty and None geometries return -1.

Parameters `geometry` : Geometry or array_like

Examples

```
>>> get_dimensions(Geometry("POINT (0 0)"))
0
>>> get_dimensions(Geometry("POLYGON((0 0, 0 10, 10 10, 10 0, 0 0))"))
2
>>> get_dimensions(Geometry("GEOMETRYCOLLECTION (POINT(0 0), LINESTRING(0 0, 1 1))
↪"))
1
>>> get_dimensions(Geometry("GEOMETRYCOLLECTION EMPTY"))
-1
>>> get_dimensions(None)
-1
```

`pygeos.geometry.get_exterior_ring(geometry)`
Returns the exterior ring of a polygon.

Parameters `geometry` : Geometry or array_like

See also:

`get_interior_ring`

Examples

```
>>> get_exterior_ring(Geometry("POLYGON((0 0, 0 10, 10 10, 10 0, 0 0))"))
<pygeos.Geometry LINEARRING (0 0, 0 10, 10 10, 10 0, 0 0)>
>>> get_exterior_ring(Geometry("POINT (1 1)")) is None
True
```

`pygeos.geometry.get_geometry(geometry, index)`
Returns the nth geometry from a collection of geometries.

Parameters `geometry` : Geometry or array_like

index : int or array_like

Negative values count from the end of the collection backwards.

See also:

`get_num_geometries`

Notes

- simple geometries act as length-1 collections
- out-of-range values return None

Examples

```
>>> multipoint = Geometry("MULTIPOINT (0 0, 1 1, 2 2, 3 3)")
>>> get_geometry(multipoint, 1)
<pygeos.Geometry POINT (1 1)>
>>> get_geometry(multipoint, -1)
<pygeos.Geometry POINT (3 3)>
>>> get_geometry(multipoint, 5) is None
True
>>> get_geometry(Geometry("POINT (1 1)"), 0)
<pygeos.Geometry POINT (1 1)>
>>> get_geometry(Geometry("POINT (1 1)"), 1) is None
True
```

`pygeos.geometry.get_interior_ring(geometry, index)`
Returns the nth interior ring of a polygon.

Parameters `geometry` : Geometry or array_like

`index` : int or array_like

Negative values count from the end of the interior rings backwards.

See also:

[`get\_exterior\_ring`](#), [`get\_num\_interior\_rings`](#)

Examples

```
>>> polygon_with_hole = Geometry("POLYGON((0 0, 0 10, 10 10, 10 0, 0 0), (2 2, 2_
↪4, 4 4, 4 2, 2 2))")
>>> get_interior_ring(polygon_with_hole, 0)
<pygeos.Geometry LINEARRING (2 2, 2 4, 4 4, 4 2, 2 2)>
>>> get_interior_ring(Geometry("POINT (1 1)"), 0) is None
True
```

`pygeos.geometry.get_num_coordinates(geometry)`
Returns the total number of coordinates in a geometry.

Returns -1 for not-a-geometry values.

Parameters `geometry` : Geometry or array_like

Examples

```
>>> get_num_coordinates(Geometry("POINT (0 0)"))
1
>>> get_num_coordinates(Geometry("POINT Z (0 0 0)"))
1
>>> get_num_coordinates(Geometry("GEOMETRYCOLLECTION (POINT(0 0), LINESTRING(0 0,
↪1 1))"))
3
>>> get_num_coordinates(None)
-1
```

`pygeos.geometry.get_num_geometries(geometry)`
Returns number of geometries in a collection.

Parameters *geometry* : Geometry or array_like

The number of geometries in points, linestrings, linearrings and polygons equals one.

See also:

get_num_points, get_geometry

Examples

```
>>> get_num_geometries(Geometry("MULTIPOINT (0 0, 1 1, 2 2, 3 3)"))
4
>>> get_num_geometries(Geometry("POINT (1 1)"))
1
```

`pygeos.geometry.get_num_interior_rings(geometry)`

Returns number of internal rings in a polygon

Parameters *geometry* : Geometry or array_like

The number of interior rings in non-polygons equals zero.

See also:

get_exterior_ring, get_interior_ring

Examples

```
>>> polygon = Geometry("POLYGON((0 0, 0 10, 10 10, 10 0, 0 0))")
>>> get_num_interior_rings(polygon)
0
>>> polygon_with_hole = Geometry("POLYGON((0 0, 0 10, 10 10, 10 0, 0 0), (2 2, 2_
↪4, 4 4, 4 2, 2 2))")
>>> get_num_interior_rings(polygon_with_hole)
1
>>> get_num_interior_rings(Geometry("POINT (1 1)"))
0
```

`pygeos.geometry.get_num_points(geometry)`

Returns number of points in a linestring or linearring.

Parameters *geometry* : Geometry or array_like

The number of points in geometries other than linestring or linearring equals zero.

See also:

get_point, get_num_geometries

Examples

```
>>> line = Geometry("LINESTRING (0 0, 1 1, 2 2, 3 3)")
>>> get_num_points(line)
4
>>> get_num_points(Geometry("MULTIPOINT (0 0, 1 1, 2 2, 3 3)"))
0
```

`pygeos.geometry.get_point(geometry, index)`

Returns the *nth* point of a linestring or linearring.

Parameters `geometry` : Geometry or array_like

`index` : int or array_like

Negative values count from the end of the linestring backwards.

See also:

[`get\_num\_points`](#)

Examples

```
>>> line = Geometry("LINESTRING (0 0, 1 1, 2 2, 3 3)")
>>> get_point(line, 1)
<pygeos.Geometry POINT (1 1)>
>>> get_point(line, -2)
<pygeos.Geometry POINT (2 2)>
>>> get_point(line, [0, 3]).tolist()
[<pygeos.Geometry POINT (0 0)>, <pygeos.Geometry POINT (3 3)>]
>>> get_point(Geometry("LINEARRING (0 0, 1 1, 2 2, 0 0)"), 1)
<pygeos.Geometry POINT (1 1)>
>>> get_point(Geometry("MULTIPOINT (0 0, 1 1, 2 2, 3 3)"), 1) is None
True
>>> get_point(Geometry("POINT (1 1)"), 0) is None
True
```

`pygeos.geometry.get_srid(geometry)`

Returns the SRID of a geometry.

Returns -1 for not-a-geometry values.

Parameters `geometry` : Geometry or array_like

See also:

[`set\_srid`](#)

Examples

```
>>> point = Geometry("POINT (0 0)")
>>> with_srid = set_srid(point, 4326)
>>> get_srid(point)
0
>>> get_srid(with_srid)
4326
```

`pygeos.geometry.get_type_id(geometry)`

Returns the type ID of a geometry.

- None is -1
- POINT is 0
- LINESTRING is 1
- LINEARRING is 2
- POLYGON is 3
- MULTIPOINT is 4
- MULTILINESTRING is 5
- MULTIPOLYGON is 6
- GEOMETRYCOLLECTION is 7

Parameters `geometry` : Geometry or array_like

See also:

`GeometryType`

Examples

```
>>> get_type_id(Geometry("LINESTRING (0 0, 1 1, 2 2, 3 3)"))
1
>>> get_type_id([Geometry("POINT (1 2)"), Geometry("POINT (1 2)")]).tolist()
[0, 0]
```

`pygeos.geometry.get_x(point)`

Returns the x-coordinate of a point

Parameters `point` : Geometry or array_like

Non-point geometries will result in NaN being returned.

See also:

`get_y`

Examples

```
>>> get_x(Geometry("POINT (1 2)"))
1.0
>>> get_x(Geometry("MULTIPOINT (1 1, 1 2)"))
nan
```

`pygeos.geometry.get_y(point)`

Returns the y-coordinate of a point

Parameters `point` : Geometry or array_like

Non-point geometries will result in NaN being returned.

See also:

`get_x`

Examples

```
>>> get_y(Geometry("POINT (1 2)"))
2.0
>>> get_y(Geometry("MULTIPOINT (1 1, 1 2)"))
nan
```

`pygeos.geometry.set_srid(geometry, srid)`

Returns a geometry with its SRID set.

Parameters `geometry` : Geometry or array_like

`srid` : int

See also:

`get_srid`

Examples

```
>>> point = Geometry("POINT (0 0)")
>>> with_srid = set_srid(point, 4326)
>>> get_srid(point)
0
>>> get_srid(with_srid)
4326
```

3.4 pygeos.linear

`pygeos.linear.line_interpolate_point(line, distance, normalize=False)`

Returns a point interpolated at given distance on a line.

Parameters `line` : Geometry or array_like

`distance` : float or array_like

Negative values measure distance from the end of the line. Out-of-range values will be clipped to the line endings.

`normalize` : bool

If `normalize` is set to `True`, the distance is a fraction of the total line length instead of the absolute distance.

Examples

```
>>> line = Geometry("LINESTRING(0 2, 0 10)")
>>> line_interpolate_point(line, 2)
<pygeos.Geometry POINT (0 4)>
>>> line_interpolate_point(line, 100)
<pygeos.Geometry POINT (0 10)>
>>> line_interpolate_point(line, -2)
<pygeos.Geometry POINT (0 8)>
>>> line_interpolate_point(line, [0.25, -0.25], normalize=True).tolist()
[<pygeos.Geometry POINT (0 4)>, <pygeos.Geometry POINT (0 8)>]
```

(continues on next page)

(continued from previous page)

```
>>> line_interpolate_point(Geometry("LINESTRING EMPTY"), 1)
<pygeos.Geometry POINT EMPTY>
```

`pygeos.linear.line_locate_point(line, other, normalize=False)`

Returns the distance to the line origin of given point.

If given point does not intersect with the line, the point will first be projected onto the line after which the distance is taken.

Parameters `line` : Geometry or array_like

`point` : Geometry or array_like

`normalize` : bool

If `normalize` is set to `True`, the distance is a fraction of the total line length instead of the absolute distance.

Examples

```
>>> line = Geometry("LINESTRING(0 2, 0 10)")
>>> line_locate_point(line, Geometry("POINT(4 4)"))
2.0
>>> line_locate_point(line, Geometry("POINT(4 4)"), normalize=True)
0.25
>>> line_locate_point(line, Geometry("POINT(0 18)"))
8.0
>>> line_locate_point(Geometry("LINESTRING EMPTY"), Geometry("POINT(4 4)"))
nan
```

`pygeos.linear.line_merge(line)`

Returns (multi)linestrings formed by combining the lines in a multilinestrings.

Parameters `line` : Geometry or array_like

Examples

```
>>> line_merge(Geometry("MULTILINESTRING((0 2, 0 10), (0 10, 5 10))"))
<pygeos.Geometry LINESTRING (0 2, 0 10, 5 10)>
>>> line_merge(Geometry("MULTILINESTRING((0 2, 0 10), (0 11, 5 10))"))
<pygeos.Geometry MULTILINESTRING ((0 2, 0 10), (0 11, 5 10))>
>>> line_merge(Geometry("LINESTRING EMPTY"))
<pygeos.Geometry GEOMETRYCOLLECTION EMPTY>
```

`pygeos.linear.shared_paths(a, b, **kwargs)`

Returns the shared paths between `geom1` and `geom2`.

Both geometries should be linestrings or arrays of linestrings. A geometrycollection or array of geometrycollections is returned with two elements in each geometrycollection. The first element is a multilinestring containing shared paths with the same direction for both inputs. The second element is a multilinestring containing shared paths with the opposite direction for the two inputs.

Parameters `a` : Geometry or array_like

`b` : Geometry or array_like

Examples

```
>>> geom1 = Geometry("LINESTRING (0 0, 1 0, 1 1, 0 1, 0 0)")
>>> geom2 = Geometry("LINESTRING (1 0, 2 0, 2 1, 1 1, 1 0)")
>>> shared_paths(geom1, geom2)
<pygeos.Geometry GEOMETRYCOLLECTION (MULTILINESTRING EMPTY, MULTILINESTRING ((1 0,
↪ 1 1)))>
```

3.5 pygeos.measurement

`pygeos.measurement.area(geometry, **kwargs)`

Computes the area of a (multi)polygon.

Parameters `geometry` : Geometry or array_like

Examples

```
>>> area(Geometry("POLYGON((0 0, 0 10, 10 10, 10 0, 0 0))"))
100.0
>>> area(Geometry("MULTIPOLYGON (((0 0, 0 10, 10 10, 0 0)), ((0 0, 0 10, 10 10, 0_
↪ 0)))"))
100.0
>>> area(Geometry("POLYGON EMPTY"))
0.0
>>> area(None)
nan
```

`pygeos.measurement.bounds(geometry, **kwargs)`

Computes the bounds (extent) of a geometry.

For each geometry these 4 numbers are returned: min x, min y, max x, max y.

Parameters `geometry` : Geometry or array_like

Examples

```
>>> bounds(Geometry("POINT (2 3)").tolist()
[2.0, 3.0, 2.0, 3.0]
>>> bounds(Geometry("LINESTRING (0 0, 0 2, 3 2)").tolist()
[0.0, 0.0, 3.0, 2.0]
>>> bounds(Geometry("POLYGON EMPTY")).tolist()
[nan, nan, nan, nan]
>>> bounds(None).tolist()
[nan, nan, nan, nan]
```

`pygeos.measurement.distance(a, b, **kwargs)`

Computes the Cartesian distance between two geometries.

Parameters `a, b` : Geometry or array_like

Examples

```
>>> point = Geometry("POINT (0 0)")
>>> distance(Geometry("POINT (10 0)"), point)
10.0
>>> distance(Geometry("LINESTRING (1 1, 1 -1)"), point)
1.0
>>> distance(Geometry("POLYGON ((3 0, 5 0, 5 5, 3 5, 3 0))"), point)
3.0
>>> distance(Geometry("POINT EMPTY"), point)
nan
>>> distance(None, point)
nan
```

`pygeos.measurement.hausdorff_distance(a, b, densify=None, **kwargs)`
 Compute the discrete Hausdorff distance between two geometries.

The Hausdorff distance is a measure of similarity: it is the greatest distance between any point in A and the closest point in B. The discrete distance is an approximation of this metric: only vertices are considered. The parameter ‘densify’ makes this approximation less coarse by splitting the line segments between vertices before computing the distance.

Parameters *a, b* : Geometry or array_like

densify : float, array_like or None

The value of densify is required to be between 0 and 1.

Examples

```
>>> line_1 = Geometry("LINESTRING (130 0, 0 0, 0 150)")
>>> line_2 = Geometry("LINESTRING (10 10, 10 150, 130 10)")
>>> hausdorff_distance(line_1, line_2)
14.14...
>>> hausdorff_distance(line_1, line_2, densify=0.5)
70.0
>>> hausdorff_distance(line_1, Geometry("LINESTRING EMPTY"))
nan
>>> hausdorff_distance(line_1, None)
nan
```

`pygeos.measurement.length(geometry, **kwargs)`
 Computes the length of a (multi)linestring or polygon perimeter.

Parameters *geometry* : Geometry or array_like

Examples

```
>>> length(Geometry("LINESTRING (0 0, 0 2, 3 2)"))
5.0
>>> length(Geometry("MULTILINESTRING ((0 0, 1 0), (0 0, 1 0))"))
2.0
>>> length(Geometry("POLYGON((0 0, 0 10, 10 10, 10 0, 0 0))"))
40.0
>>> length(Geometry("LINESTRING EMPTY"))
0.0
```

(continues on next page)

(continued from previous page)

```
>>> length(None)
nan
```

3.6 pygeos.predicates

`pygeos.predicates.contains(a, b, **kwargs)`

Returns True if geometry B is completely inside geometry A.

A contains B if no points of B lie in the exterior of A and at least one point of the interior of B lies in the interior of A.

Parameters *a, b* : Geometry or array_like

See also:

`within` `contains(A, B) == within(B, A)`

Examples

```
>>> line = Geometry("LINESTRING(0 0, 1 1)")
>>> contains(line, Geometry("POINT (0 0)"))
False
>>> contains(line, Geometry("POINT (0.5 0.5)"))
True
>>> area = Geometry("POLYGON((0 0, 1 0, 1 1, 0 1, 0 0))")
>>> contains(area, Geometry("POINT (0 0)"))
False
>>> contains(area, line)
True
>>> contains(area, Geometry("LINESTRING(0 0, 2 2)"))
False
>>> polygon_with_hole = Geometry("POLYGON((0 0, 10 0, 10 10, 0 10, 0 0), (2 2, 4
↳2, 4 4, 2 4, 2 2))")
>>> contains(polygon_with_hole, Geometry("POINT(1 1)"))
True
>>> contains(polygon_with_hole, Geometry("POINT(2 2)"))
False
>>> contains(polygon_with_hole, Geometry("LINESTRING(1 1, 5 5)"))
False
>>> contains(area, area)
True
>>> contains(area, None)
False
```

`pygeos.predicates.covered_by(a, b, **kwargs)`

Returns True if no point in geometry A is outside geometry B.

Parameters *a, b* : Geometry or array_like

See also:

`covers` `covered_by(A, B) == covers(B, A)`

Examples

```
>>> line = Geometry("LINESTRING(0 0, 1 1)")
>>> covered_by(Geometry("POINT (0 0)"), line)
True
>>> covered_by(Geometry("POINT (0.5 0.5)"), line)
True
>>> area = Geometry("POLYGON((0 0, 1 0, 1 1, 0 1, 0 0))")
>>> covered_by(Geometry("POINT (0 0)"), area)
True
>>> covered_by(line, area)
True
>>> covered_by(Geometry("LINESTRING(0 0, 2 2)"), area)
False
>>> polygon_with_hole = Geometry("POLYGON((0 0, 10 0, 10 10, 0 10, 0 0), (2 2, 4
↪2, 4 4, 2 4, 2 2))") # NOQA
>>> covered_by(Geometry("POINT(1 1)"), polygon_with_hole)
True
>>> covered_by(Geometry("POINT(2 2)"), polygon_with_hole)
True
>>> covered_by(Geometry("LINESTRING(1 1, 5 5)"), polygon_with_hole)
False
>>> covered_by(area, area)
True
>>> covered_by(None, area)
False
```

`pygeos.predicates.covers(a, b, **kwargs)`

Returns True if no point in geometry B is outside geometry A.

Parameters *a, b* : Geometry or array_like

See also:

`covered_by` `covers(A, B) == covered_by(B, A)`

Examples

```
>>> line = Geometry("LINESTRING(0 0, 1 1)")
>>> covers(line, Geometry("POINT (0 0)"))
True
>>> covers(line, Geometry("POINT (0.5 0.5)"))
True
>>> area = Geometry("POLYGON((0 0, 1 0, 1 1, 0 1, 0 0))")
>>> covers(area, Geometry("POINT (0 0)"))
True
>>> covers(area, line)
True
>>> covers(area, Geometry("LINESTRING(0 0, 2 2)"))
False
>>> polygon_with_hole = Geometry("POLYGON((0 0, 10 0, 10 10, 0 10, 0 0), (2 2, 4
↪2, 4 4, 2 4, 2 2))") # NOQA
>>> covers(polygon_with_hole, Geometry("POINT(1 1)"))
True
>>> covers(polygon_with_hole, Geometry("POINT(2 2)"))
True
```

(continues on next page)

(continued from previous page)

```
>>> covers(polygon_with_hole, Geometry("LINESTRING(1 1, 5 5)"))
False
>>> covers(area, area)
True
>>> covers(area, None)
False
```

`pygeos.predicates.crosses(a, b, **kwargs)`

Returns True if the intersection of two geometries spatially crosses.

That is: the geometries have some, but not all interior points in common. The geometries must intersect and the intersection must have a dimensionality less than the maximum dimension of the two input geometries. Additionally, the intersection of the two geometries must not equal either of the source geometries.

Parameters *a, b* : Geometry or array_like

Examples

```
>>> line = Geometry("LINESTRING(0 0, 1 1)")
>>> crosses(line, Geometry("POINT (0.5 0.5)"))
False
>>> crosses(line, Geometry("MULTIPOINT ((0 1), (0.5 0.5))"))
True
>>> crosses(line, Geometry("LINESTRING(0 1, 1 0)"))
True
>>> crosses(line, Geometry("LINESTRING(0 0, 2 2)"))
False
>>> area = Geometry("POLYGON((0 0, 1 0, 1 1, 0 1, 0 0))")
>>> crosses(area, line)
False
>>> crosses(area, Geometry("LINESTRING(0 0, 2 2)"))
True
>>> crosses(area, Geometry("POINT (0.5 0.5)"))
False
>>> crosses(area, Geometry("MULTIPOINT ((2 2), (0.5 0.5))"))
True
```

`pygeos.predicates.disjoint(a, b, **kwargs)`

Returns True if A and B do not share any point in space.

Disjoint implies that overlaps, touches, within, and intersects are False. Note missing (None) values are never disjoint.

Parameters *a, b* : Geometry or array_like

See also:

`intersects disjoint(A, B) == ~intersects(A, B)`

Examples

```
>>> line = Geometry("LINESTRING(0 0, 1 1)")
>>> disjoint(line, Geometry("POINT (0 0)"))
False
>>> disjoint(line, Geometry("POINT (0 1)"))
True
>>> disjoint(line, Geometry("LINESTRING(0 2, 2 0)"))
False
>>> empty = Geometry("GEOMETRYCOLLECTION EMPTY")
>>> disjoint(line, empty)
True
>>> disjoint(empty, empty)
True
>>> disjoint(empty, None)
False
>>> disjoint(None, None)
False
```

`pygeos.predicates.equals(a, b, **kwargs)`

Returns True if A and B are spatially equal.

If A is within B and B is within A, A and B are considered equal. The ordering of points can be different.

Parameters *a, b* : Geometry or array_like

See also:

[`equals\_exact`](#) Check if A and B are structurally equal given a specified tolerance.

Examples

```
>>> line = Geometry("LINESTRING(0 0, 5 5, 10 10)")
>>> equals(line, Geometry("LINESTRING(0 0, 10 10)"))
True
>>> equals(Geometry("POLYGON EMPTY"), Geometry("GEOMETRYCOLLECTION EMPTY"))
True
>>> equals(None, None)
False
```

`pygeos.predicates.equals_exact(a, b, tolerance=0.0, **kwargs)`

Returns True if A and B are structurally equal.

This method uses exact coordinate equality, which requires coordinates to be equal (within specified tolerance) and in the same order for all components of a geometry. This is in contrast with the `equals` function which uses spatial (topological) equality.

Parameters *a, b* : Geometry or array_like

tolerance : float or array_like

See also:

[`equals`](#) Check if A and B are spatially equal.

Examples

```
>>> point1 = Geometry("POINT(50 50)")
>>> point2 = Geometry("POINT(50.1 50.1)")
>>> equals_exact(point1, point2)
False
>>> equals_exact(point1, point2, tolerance=0.2)
True
>>> equals_exact(point1, None, tolerance=0.2)
False
```

Difference between structural and spatial equality:

```
>>> polygon1 = Geometry("POLYGON((0 0, 1 1, 0 1, 0 0))")
>>> polygon2 = Geometry("POLYGON((0 0, 0 1, 1 1, 0 0))")
>>> equals_exact(polygon1, polygon2)
False
>>> equals(polygon1, polygon2)
True
```

`pygeos.predicates.has_z(geometry, **kwargs)`

Returns True if a geometry has a Z coordinate.

Parameters `geometry` : Geometry or array_like

Examples

```
>>> has_z(Geometry("POINT (0 0)"))
False
>>> has_z(Geometry("POINT Z (0 0 0)"))
True
```

`pygeos.predicates.intersects(a, b, **kwargs)`

Returns True if A and B share any portion of space.

Intersects implies that overlaps, touches and within are True.

Parameters `a, b` : Geometry or array_like

See also:

`disjoint intersects(A, B) == ~disjoint(A, B)`

Examples

```
>>> line = Geometry("LINESTRING(0 0, 1 1)")
>>> intersects(line, Geometry("POINT (0 0)"))
True
>>> intersects(line, Geometry("POINT (0 1)"))
False
>>> intersects(line, Geometry("LINESTRING(0 2, 2 0)"))
True
>>> intersects(None, None)
False
```


`pygeos.predicates.is_closed(geometry, **kwargs)`
Returns True if a linestring's first and last points are equal.

Parameters `geometry` : Geometry or array_like

This function will return False for non-linestrings.

See also:

[`is\_ring`](#) Checks additionally if the geometry is simple.

Examples

```
>>> is_closed(Geometry("LINESTRING (0 0, 1 1)"))
False
>>> is_closed(Geometry("LINESTRING(0 0, 0 1, 1 1, 0 0)"))
True
>>> is_closed(Geometry("POINT (0 0)"))
False
```

`pygeos.predicates.is_empty(geometry, **kwargs)`
Returns True if a geometry is an empty point, polygon, etc.

Parameters `geometry` : Geometry or array_like

Any geometry type is accepted.

See also:

[`is\_missing`](#) checks if the object is a geometry

Examples

```
>>> is_empty(Geometry("POINT EMPTY"))
True
>>> is_empty(Geometry("POINT (0 0)"))
False
>>> is_empty(None)
False
```

`pygeos.predicates.is_geometry(geometry, **kwargs)`
Returns True if the object is a geometry

Parameters `geometry` : any object or array_like

See also:

[`is\_missing`](#) check if an object is missing (None)

[`is\_valid\_input`](#) check if an object is a geometry or None

Examples

```
>>> is_geometry(Geometry("POINT (0 0)"))
True
>>> is_geometry(Geometry("GEOMETRYCOLLECTION EMPTY"))
True
>>> is_geometry(None)
False
>>> is_geometry("text")
False
```

`pygeos.predicates.is_missing(geometry, **kwargs)`

Returns True if the object is not a geometry (None)

Parameters `geometry` : any object or array_like

See also:

[`is\_geometry`](#) check if an object is a geometry

[`is\_valid\_input`](#) check if an object is a geometry or None

[`is\_empty`](#) checks if the object is an empty geometry

Examples

```
>>> is_missing(Geometry("POINT (0 0)"))
False
>>> is_missing(Geometry("GEOMETRYCOLLECTION EMPTY"))
False
>>> is_missing(None)
True
>>> is_missing("text")
False
```

`pygeos.predicates.is_ring(geometry, **kwargs)`

Returns True if a linestring is closed and simple.

Parameters `geometry` : Geometry or array_like

This function will return False for non-linestrings.

See also:

[`is\_closed`](#) Checks only if the geometry is closed.

[`is\_simple`](#) Checks only if the geometry is simple.

Examples

```
>>> is_ring(Geometry("POINT (0 0)"))
False
>>> geom = Geometry("LINESTRING(0 0, 1 1)")
>>> is_closed(geom), is_simple(geom), is_ring(geom)
(False, True, False)
>>> geom = Geometry("LINESTRING(0 0, 0 1, 1 1, 0 0)")
>>> is_closed(geom), is_simple(geom), is_ring(geom)
(True, True, True)
>>> geom = Geometry("LINESTRING(0 0, 1 1, 0 1, 1 0, 0 0)")
>>> is_closed(geom), is_simple(geom), is_ring(geom)
(True, False, False)
```

`pygeos.predicates.is_simple(geometry, **kwargs)`

Returns True if a Geometry has no anomalous geometric points, such as self-intersections or self tangency.

Parameters `geometry` : Geometry or array_like

This function will return False for geometrycollections.

See also:

[`is\_ring`](#) Checks additionally if the geometry is closed.

Examples

```
>>> is_simple(Geometry("POLYGON((1 1, 2 1, 2 2, 1 1))"))
True
>>> is_simple(Geometry("LINESTRING(0 0, 1 1, 0 1, 1 0, 0 0)"))
False
>>> is_simple(None)
False
```

`pygeos.predicates.is_valid(geometry, **kwargs)`

Returns True if a geometry is well formed.

Parameters `geometry` : Geometry or array_like

Any geometry type is accepted. Returns False for missing values.

See also:

[`is\_valid\_reason`](#) Returns the reason in case of invalid.

Examples

```
>>> is_valid(Geometry("LINESTRING(0 0, 1 1)"))
True
>>> is_valid(Geometry("POLYGON((0 0, 1 1, 1 2, 1 1, 0 0))"))
False
>>> is_valid(Geometry("GEOMETRYCOLLECTION EMPTY"))
True
>>> is_valid(None)
False
```

`pygeos.predicates.is_valid_input(geometry, **kwargs)`

Returns True if the object is a geometry or None

Parameters `geometry` : any object or array_like

See also:

`is_geometry` checks if an object is a geometry

`is_missing` checks if an object is None

Examples

```
>>> is_valid_input(Geometry("POINT (0 0)"))
True
>>> is_valid_input(Geometry("GEOMETRYCOLLECTION EMPTY"))
True
>>> is_valid_input(None)
True
>>> is_valid_input(1.0)
False
>>> is_valid_input("text")
False
```

`pygeos.predicates.is_valid_reason(geometry, **kwargs)`

Returns a string stating if a geometry is valid and if not, why.

Parameters `geometry` : Geometry or array_like

Any geometry type is accepted. Returns None for missing values.

See also:

`is_valid` returns True or False

Examples

```
>>> is_valid_reason(Geometry("LINESTRING(0 0, 1 1)"))
'Valid Geometry'
>>> is_valid_reason(Geometry("POLYGON((0 0, 1 1, 1 2, 1 1, 0 0))"))
'Self-intersection[0 0]'
>>> is_valid_reason(None) is None
True
```

`pygeos.predicates.overlaps(a, b, **kwargs)`

Returns True if A and B intersect, but one does not completely contain the other.

Parameters `a, b` : Geometry or array_like

Examples

```
>>> line = Geometry("LINESTRING(0 0, 1 1)")
>>> overlaps(line, line)
False
>>> overlaps(line, Geometry("LINESTRING(0 0, 2 2)"))
False
>>> overlaps(line, Geometry("LINESTRING(0.5 0.5, 2 2)"))
True
>>> overlaps(line, Geometry("POINT (0.5 0.5)"))
False
>>> overlaps(None, None)
False
```

`pygeos.predicates.touches(a, b, **kwargs)`

Returns True if the only points shared between A and B are on the boundary of A and B.

Parameters *a, b* : Geometry or array_like

Examples

```
>>> line = Geometry("LINESTRING(0 2, 2 0)")
>>> touches(line, Geometry("POINT(0 2)"))
True
>>> touches(line, Geometry("POINT(1 1)"))
False
>>> touches(line, Geometry("LINESTRING(0 0, 1 1)"))
True
>>> touches(line, Geometry("LINESTRING(0 0, 2 2)"))
False
>>> area = Geometry("POLYGON((0 0, 1 0, 1 1, 0 1, 0 0))")
>>> touches(area, Geometry("POINT(0.5 0)"))
True
>>> touches(area, Geometry("POINT(0.5 0.5)"))
False
>>> touches(area, line)
True
>>> touches(area, Geometry("POLYGON((0 1, 1 1, 1 2, 0 2, 0 1))"))
True
```

`pygeos.predicates.within(a, b, **kwargs)`

Returns True if geometry A is completely inside geometry B.

A is within B if no points of A lie in the exterior of B and at least one point of the interior of A lies in the interior of B.

Parameters *a, b* : Geometry or array_like

See also:

`contains` `within(A, B) == contains(B, A)`

Examples

```
>>> line = Geometry("LINESTRING(0 0, 1 1)")
>>> within(Geometry("POINT (0 0)"), line)
False
>>> within(Geometry("POINT (0.5 0.5)"), line)
True
>>> area = Geometry("POLYGON((0 0, 1 0, 1 1, 0 1, 0 0))")
>>> within(Geometry("POINT (0 0)"), area)
False
>>> within(line, area)
True
>>> within(Geometry("LINESTRING(0 0, 2 2)"), area)
False
>>> polygon_with_hole = Geometry("POLYGON((0 0, 10 0, 10 10, 0 10, 0 0), (2 2, 4
↪2, 4 4, 2 4, 2 2))") # NOQA
>>> within(Geometry("POINT(1 1)"), polygon_with_hole)
True
>>> within(Geometry("POINT(2 2)"), polygon_with_hole)
False
>>> within(Geometry("LINESTRING(1 1, 5 5)"), polygon_with_hole)
False
>>> within(area, area)
True
>>> within(None, area)
False
```

3.7 pygeos.set_operations

`pygeos.set_operations.difference(a, b, **kwargs)`

Returns the part of geometry A that does not intersect with geometry B.

Parameters **a** : Geometry or array_like

b : Geometry or array_like

Examples

```
>>> line = Geometry("LINESTRING (0 0, 2 2)")
>>> difference(line, Geometry("LINESTRING (1 1, 3 3)"))
<pygeos.Geometry LINESTRING (0 0, 1 1)>
>>> difference(line, Geometry("LINESTRING EMPTY"))
<pygeos.Geometry LINESTRING (0 0, 2 2)>
>>> difference(line, None) is None
True
```

`pygeos.set_operations.intersection(a, b, **kwargs)`

Returns the geometry that is shared between input geometries.

Parameters **a** : Geometry or array_like

b : Geometry or array_like

See also:

[`intersection\_all`](#)

Examples

```
>>> line = Geometry("LINESTRING(0 0, 2 2)")
>>> intersection(line, Geometry("LINESTRING(1 1, 3 3)"))
<pygeos.Geometry LINESTRING (1 1, 2 2)>
```

`pygeos.set_operations.intersection_all` (*geometries*, *axis=0*, ***kwargs*)

Returns the intersection of multiple geometries.

Parameters *geometries* : array_like

axis : int

Axis along which the operation is performed. The default (zero) performs the operation over the first dimension of the input array. *axis* may be negative, in which case it counts from the last to the first axis.

See also:

intersection

Examples

```
>>> line_1 = Geometry("LINESTRING(0 0, 2 2)")
>>> line_2 = Geometry("LINESTRING(1 1, 3 3)")
>>> intersection_all([line_1, line_2])
<pygeos.Geometry LINESTRING (1 1, 2 2)>
>>> intersection_all([line_1, line_2, None], axis=1).tolist()
[None]
```

`pygeos.set_operations.symmetric_difference` (*a*, *b*, ***kwargs*)

Returns the geometry that represents the portions of input geometries that do not intersect.

Parameters *a* : Geometry or array_like

b : Geometry or array_like

See also:

symmetric_difference_all

Examples

```
>>> line = Geometry("LINESTRING(0 0, 2 2)")
>>> symmetric_difference(line, Geometry("LINESTRING(1 1, 3 3)"))
<pygeos.Geometry MULTILINESTRING ((0 0, 1 1), (2 2, 3 3))>
```

`pygeos.set_operations.symmetric_difference_all` (*geometries*, *axis=0*, ***kwargs*)

Returns the symmetric difference of multiple geometries.

Parameters *geometries* : array_like

axis : int

Axis along which the operation is performed. The default (zero) performs the operation over the first dimension of the input array. *axis* may be negative, in which case it counts from the last to the first axis.

See also:

[symmetric_difference](#)

Examples

```
>>> line_1 = Geometry("LINESTRING(0 0, 2 2)")
>>> line_2 = Geometry("LINESTRING(1 1, 3 3)")
>>> symmetric_difference_all([line_1, line_2])
<pygeos.Geometry MULTILINESTRING ((0 0, 1 1), (2 2, 3 3))>
>>> symmetric_difference_all([[line_1, line_2, None]], axis=1).tolist()
[None]
```

`pygeos.set_operations.union(a, b, **kwargs)`

Merges geometries into one.

Parameters **a** : Geometry or array_like

b : Geometry or array_like

See also:

[union_all](#)

Examples

```
>>> line = Geometry("LINESTRING(0 0, 2 2)")
>>> union(line, Geometry("LINESTRING(2 2, 3 3)"))
<pygeos.Geometry MULTILINESTRING ((0 0, 2 2), (2 2, 3 3))>
>>> union(line, None) is None
True
```

`pygeos.set_operations.union_all(geometries, axis=0, **kwargs)`

Returns the union of multiple geometries.

Parameters **geometries** : array_like

axis : int

Axis along which the operation is performed. The default (zero) performs the operation over the first dimension of the input array. axis may be negative, in which case it counts from the last to the first axis.

See also:

[union](#)

Examples

```
>>> line_1 = Geometry("LINESTRING(0 0, 2 2)")
>>> line_2 = Geometry("LINESTRING(2 2, 3 3)")
>>> union_all([line_1, line_2])
<pygeos.Geometry MULTILINESTRING ((0 0, 2 2), (2 2, 3 3))>
>>> union_all([[line_1, line_2, None]], axis=1).tolist()
[<pygeos.Geometry MULTILINESTRING ((0 0, 2 2), (2 2, 3 3))>]
```


3.8 pygeos.strtree

class pygeos.strtree.**STRtree**(*geometries*, *leafsize*=5)

Bases: object

A query-only R-tree created using the Sort-Tile-Recursive (STR) algorithm.

For two-dimensional spatial data. The actual tree will be constructed at the first query.

Parameters *geometries* : array_like

leafsize : int

the maximum number of child nodes that a node can have

Examples

```
>>> import pygeos
>>> geoms = pygeos.points(np.arange(10), np.arange(10))
>>> tree = pygeos.STRtree(geoms)
>>> tree.query(pygeos.box(2, 2, 4, 4)).tolist()
[2, 3, 4]
```

Attributes

Methods

__init__(*geometries*, *leafsize*=5)

Initialize self. See help(type(self)) for accurate signature.

__weakref__

list of weak references to the object (if defined)

query(*envelope*)

Return all items whose extent intersect the given envelope.

Parameters *envelope* : Geometry

The envelope of the geometry is taken automatically.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

p

- `pygeos.constructive`, [7](#)
- `pygeos.coordinates`, [13](#)
- `pygeos.geometry`, [14](#)
- `pygeos.linear`, [20](#)
- `pygeos.measurement`, [22](#)
- `pygeos.predicates`, [24](#)
- `pygeos.set_operations`, [34](#)
- `pygeos.strtree`, [37](#)

Symbols

`__init__()` (*pygeos.stree.STRtree method*), 37
`__weakref__` (*pygeos.stree.STRtree attribute*), 37

A

`apply()` (*in module pygeos.coordinates*), 13
`area()` (*in module pygeos.measurement*), 22

B

`boundary()` (*in module pygeos.constructive*), 7
`bounds()` (*in module pygeos.measurement*), 22
`buffer()` (*in module pygeos.constructive*), 7

C

`centroid()` (*in module pygeos.constructive*), 8
`contains()` (*in module pygeos.predicates*), 24
`convex_hull()` (*in module pygeos.constructive*), 9
`count_coordinates()` (*in module pygeos.coordinates*), 13
`covered_by()` (*in module pygeos.predicates*), 24
`covers()` (*in module pygeos.predicates*), 25
`crosses()` (*in module pygeos.predicates*), 26

D

`delaunay_triangles()` (*in module pygeos.constructive*), 9
`difference()` (*in module pygeos.set_operations*), 34
`disjoint()` (*in module pygeos.predicates*), 26
`distance()` (*in module pygeos.measurement*), 22

E

`envelope()` (*in module pygeos.constructive*), 10
`equals()` (*in module pygeos.predicates*), 27
`equals_exact()` (*in module pygeos.predicates*), 27
`extract_unique_points()` (*in module pygeos.constructive*), 10

G

`get_coordinate_dimensions()` (*in module pygeos.geometry*), 14

`get_coordinates()` (*in module pygeos.coordinates*), 13
`get_dimensions()` (*in module pygeos.geometry*), 14
`get_exterior_ring()` (*in module pygeos.geometry*), 15
`get_geometry()` (*in module pygeos.geometry*), 15
`get_interior_ring()` (*in module pygeos.geometry*), 16
`get_num_coordinates()` (*in module pygeos.geometry*), 16
`get_num_geometries()` (*in module pygeos.geometry*), 16
`get_num_interior_rings()` (*in module pygeos.geometry*), 17
`get_num_points()` (*in module pygeos.geometry*), 17
`get_point()` (*in module pygeos.geometry*), 18
`get_srid()` (*in module pygeos.geometry*), 18
`get_type_id()` (*in module pygeos.geometry*), 18
`get_x()` (*in module pygeos.geometry*), 19
`get_y()` (*in module pygeos.geometry*), 19

H

`has_z()` (*in module pygeos.predicates*), 28
`hausdorff_distance()` (*in module pygeos.measurement*), 23

I

`intersection()` (*in module pygeos.set_operations*), 34
`intersection_all()` (*in module pygeos.set_operations*), 35
`intersects()` (*in module pygeos.predicates*), 28
`is_closed()` (*in module pygeos.predicates*), 28
`is_empty()` (*in module pygeos.predicates*), 29
`is_geometry()` (*in module pygeos.predicates*), 29
`is_missing()` (*in module pygeos.predicates*), 30
`is_ring()` (*in module pygeos.predicates*), 30
`is_simple()` (*in module pygeos.predicates*), 31
`is_valid()` (*in module pygeos.predicates*), 31
`is_valid_input()` (*in module pygeos.predicates*), 31

`is_valid_reason()` (in module *pygeos.predicates*), 32

L

`length()` (in module *pygeos.measurement*), 23

`line_interpolate_point()` (in module *pygeos.linear*), 20

`line_locate_point()` (in module *pygeos.linear*), 21

`line_merge()` (in module *pygeos.linear*), 21

M

module

`pygeos.constructive`, 7

`pygeos.coordinates`, 13

`pygeos.geometry`, 14

`pygeos.linear`, 20

`pygeos.measurement`, 22

`pygeos.predicates`, 24

`pygeos.set_operations`, 34

`pygeos.strtree`, 37

O

`overlaps()` (in module *pygeos.predicates*), 32

P

`point_on_surface()` (in module *pygeos.constructive*), 10

`pygeos.constructive`
module, 7

`pygeos.coordinates`
module, 13

`pygeos.geometry`
module, 14

`pygeos.linear`
module, 20

`pygeos.measurement`
module, 22

`pygeos.predicates`
module, 24

`pygeos.set_operations`
module, 34

`pygeos.strtree`
module, 37

Q

`query()` (*pygeos.strtree.STRtree* method), 37

S

`set_coordinates()` (in module *pygeos.coordinates*), 14

`set_srid()` (in module *pygeos.geometry*), 20

`shared_paths()` (in module *pygeos.linear*), 21

`simplify()` (in module *pygeos.constructive*), 11

`snap()` (in module *pygeos.constructive*), 11

`STRtree` (class in *pygeos.strtree*), 37

`symmetric_difference()` (in module *pygeos.set_operations*), 35

`symmetric_difference_all()` (in module *pygeos.set_operations*), 35

T

`touches()` (in module *pygeos.predicates*), 33

U

`union()` (in module *pygeos.set_operations*), 36

`union_all()` (in module *pygeos.set_operations*), 36

V

`voronoi_polygons()` (in module *pygeos.constructive*), 12

W

`within()` (in module *pygeos.predicates*), 33